

Specialty Carriers

Specialty Carriers by Pride™ Lifts and Ramps are an easy, economical way to take smaller mobility products on the road. The Power Tote Mini is the perfect solution for lifting your small scooter or travel scooter for transport, while the Caddy makes bringing your manual chair along simple and inexpensive.

Caddy

- Removable sections for easy storage
- Easily mounts to Class I hitch
- 100 lbs. lifting capacity

Power Tote Mini

- Weighs just 47 lbs.
- Easily attached to Class II hitch
- 150 lbs. lifting capacity

Specialty Carriers

LIFTS CURRENT PRIDE® PRODUCTS

Caddy³

Litestream® XF
Pride® Stylus® LS
Folding Wheelchairs

Power Tote Mini³

Go-Go Elite Traveller® 3
Go-Go Elite Traveller® Plus 3
Go-Go® Ultra X 3



Call for details or visit
"Find My Compatible Lift"
at prideliftsandramps.com
for more applications.

- ¹ Weight does not include any accessories
- ² If vehicle is equipped with a Class II or III hitch, it requires a hitch reducer; additional charges apply.
- ³ Vehicle dependent
- ⁴ Requires 1.25" receiver size with 200 lbs. tongue weight

Specialty Carriers

Specialty Carriers





Caddy

Specialty Carriers

Caddy

Base weight lift	13 lbs. ¹
Maximum manual chair weight	100 lbs.
Maximum product width	N/A
Maximum travel distance from the ground	N/A
Hitch class	Class I ²
Vehicle platform	Full-size van, Mini-van, Truck, Sedan, SUV and Crossover
Warranty	3-year transferable
Lifts current Pride® products ³	Pride® Stylus® LS, Litestream® XF and other folding wheelchairs

Specialty Carriers

Power Tote Mini

Base weight lift	47 lbs. ¹
Power chair overall weight	150 lbs.
Maximum product width	22"
Maximum travel distance from the ground	20"
Motor	Sealed 12 volt DC
Hitch class	Class I ⁴ , II, III & IV
Vehicle platform	Full-size Van, Mini-van, Truck, Sedan, SUV and Crossover
Warranty	3-year transferable
Lifts current Pride® products ³	Go-Go® Ultra X (3-wheel), Go-Go Elite Traveller® (3-wheel) or Elite Traveller® Plus (3-wheel)



Power Tote Mini - PT-150

The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice.